RECEIVED CENTRALFAX'CENTER

OCT 1 2 2007

IN THE CLAIMS

Please amend the claims as follows:

1. (CURRENTLY AMENDED) A method for making a preoxidized active nickel material for a positive electrode of a hydrogen storage battery-comprising the steps of:

reacting a first reactant comprising nickel nickel sulfate with a second reactant in the presence of an oxidizing agent to form preoxidized active nickel material particles, wherein said first reactant does not comprise a hydroxide group.

2-29. (Cancelled)

- 30. (CURRENTLY AMENDED) The method of claim 1, wherein at least 1% of the preoxidized nickel material is oxidized.
- 31. (CURRENTLY AMENDED) The method of claim 1, wherein between 3% and 70% of the preoxidized nickel material is oxidized.
- 32. (CURRENTLY AMENDED) The method of claim 1, wherein between 20% and 60% of the preoxidized nickel material is oxidized.
- 33. (CURRENTLY AMENDED) The method of claim 1, wherein the preexidized nickel material comprises Ni with a +3 state of charge.

34. (CURRENTLY AMENDED) The method of claim 1, wherein said reacting step includes the steps of:

providing an active nickel material seed with a first degree of oxidation and growing a second active nickel material about the seed, the second active material about the seed having a second degree of oxidation.

35. (CANCELLED)

- 36. (PREVIOUSLY PRESENTED) The method of claim 1, wherein the oxidizing agent comprises at least one of a chlorate, a perchlorate, a hypochlorate, a hypochlorate, a peroxide, a permanganates, or a nitrate.
- 37. (PREVIOUSLY PRESENTED) The method of claim 1, wherein the oxidizing agent comprises sodium hypochlorate.
- 38. (PREVIOUSLY PRESENTED) The method of claim 1, wherein said reacting step includes the steps of:

combining a metal ion solution, ammonium solution, a metal hydroxide and an oxidant in a reactor to precipitate the active nickel material particles.

39. (PREVIOUSLY PRESENTED) The method of claim 38 wherein the metal ion solution is a metal sulfate solution.

- 40. (PREVIOUSLY PRESENTED) The method of claim 38 wherein the metal ion solution includes one or more feed streams formulated to produce active nickel material with a base metal composition consisting essentially of Ni-Co, Ni-Co-Zn, Ni-Co-Zn-Mg-Ca, and Ni-Co-Zn-Mg-Ca-Cu.
- 41. (PREVIOUSLY PRESENTED) The method of claim 1 whercin the active nickel material has a base metal composition consisting essentially of Ni-Co, Ni-Co-Zn, Ni-Co-Zn-Mg, Ni-Co-Zn-Mg-Ca, or Ni-Co-Zn-Mg-Ca-Cu.
- 42. (PREVIOUSLY PRESENTED) The method of claim 1 wherein the active nickel material particles comprise nickel hydroxide material and nickel oxyhydroxide material.
- 43. (PREVIOUSLY PRESENTED) The method of claim 1 wherein the active nickel material particles include particles that are substantially spherical.
- 44. (PREVIOUSLY PRESENTED) The method of claim 1 wherein said method produces preoxidized active nickel material with an apparent density of 1.4-1.7 g/cm³, a tap density of about 1.8-2.3 g/cm³ and an average size range of about 5-50 μm.
- 45. (PREVIOUSLY PRESENTED) The method of claim 1 wherein the active nickel material is formed with cobalt hydroxide and cobalt oxyhydroxide.

- 46. (PREVIOUSLY PRESENTED) The method of claim 1 wherein the active nickel material is provided with a surface that is less than 98% oxidized.
- 47. (PREVIOUSLY PRESENTED) The method of claim 1 wherein the active nickel material is provided with a surface that is 5% to 75% non-oxidized and the remaining portion that is oxidized.
- 48. (CURRENTLY AMENDED) A method for making preoxidized active nickel material for a positive battery electrode comprising the steps of:

providing a first reactant, said first reactant comprising nickel sulfate;

providing a second reactant, said second reactant lacking the capacity to oxidize said first reactant; and

effecting a reaction between said first reactant and said second reactant, said reaction producing said active nickel material;
wherein said reaction occurs in the presence of an oxidizing agent.

- 49. (PREVIOUSLY PRESENTED) The method of claim 48, wherein said first reactant is a nickel salt.
- 50. (CURRENTLY AMENDED) The method of claim 2048, wherein said first reactant is a liquid phase reactant.

- 2488442273
 - 51. (CURRENTLY AMENDED) The method of claim-2248, wherein said reaction is a precipitation reaction.
 - 52. (CURRENTLY AMENDED) The method of claim 2351, further comprising the step of providing a base during said reaction, said base facilitating said precipitation reaction.
 - 53. (CURRENTLY AMENDED) The method of claim 2948, wherein said second reactant is a base.
 - 54. (CURRENTLY AMENDED) The method of claim 2048, wherein said second reactant forms a complex with the nickel of said first reactant.
 - 55. (CURRENTLY AMENDED) The method of claim 2048, wherein said active nickel material comprises nickel in the +3 oxidation state.
 - 56. (CURRENTLY AMENDED) The method of claim 2748, where said active nickel material further comprises nickel in the +2 oxidation state.